



TECHNICAL DATA SHEET

APOLLO DEAD FLAT LACQUER

DESCRIPTION :

Apollo Dead Flat Lacquer is a nitro-cellulose based coating for interior application that exhibits a hard, durable & smooth matt finish.

USE :

For wood furniture, panel board, cabinets, wood trims and as topcoat for lacquer wrought iron furniture.

APPEARANCE :

Cloudly Liquid

FINISH :

Flat

APPLICATION :



Spray

REDUCTION :

Mayon Lacquer Thinner

RECOMMENDED MIXING RATIO :

1:1 (Paint : Thinner)

DRYING TIME :

Dry to touch : 10 minutes

Dry to sand / recoat : allow 20-30 minutes

COVERAGE :

8-12 sq. m. / Liter

PACKAGING :

325cc bottle; 3.75 square gallon:18L square tin can; 200L drum

SAFETY PRECAUTION :

FLAMMABLE

- Product is flammable; keep away from fire.
- Avoid vapor inhalation.
- In case of skin contact, wash immediately with soap and water; launder clothing before reuse.
- If eye contact occurs, flush with water for at least 15 minutes and call a physician.

The information in this data sheet is based on our current knowledge and experience. In view of the many factors that may affect processing and application, these data do not relieve users from the responsibility of carrying out their own tests neither do they imply any legally binding assurance of certain properties or suitability for a specific purpose. It is the responsibility of those to whom we supply our products to ensure that any propriety rights and existing laws and legislation are observed.

