



TECHNICAL DATA SHEET

APOLLO SANDING SEALER

DESCRIPTION :

Apollo Sanding Sealer is a nitro-cellulose based coating used as sealer for various types of substrates. It has exceptional sealing and hold properties for succeeding coats of clear lacquers.

It is a general purpose, high solid, high quality sealer designed for fast and easy applications.

USE :

For wood furniture, panel boards, cabinets, wood trims and other crafts.

APPEARANCE :

Sheen

APPLICATION :



Spray

RECOMMENDED THINNER :

Mayon Lacquer Thinner

RECOMMENDED MIXING RATIO :

1:1 (Paint : Thinner)

% NV :

19 ± 1

DRYING TIME :

Dry to touch : 10 minutes

Dry to sand / recoat : allow 30 minutes

COVERAGE :

8 – 12 sq. m. per liter

PACKAGING :

4L cans

SAFETY PRECAUTIONS :

FLAMMABLE

- Keep away from heat and open flame.
- Use with adequate ventilation.
- Keep container closed when not in used.
- Avoid prolonged breathing of vapor.

The information in this data sheet is based on our current knowledge and experience. In view of the many factors that may affect processing and application, these data do not relieve users from the responsibility of carrying out their own tests neither do they imply any legally binding assurance of certain properties or suitability for a specific purpose. It is the responsibility of those to whom we supply our products to ensure that any propriety rights and existing laws and legislation are observed.

