



TECHNICAL DATA SHEET

APOLLO SPRAYABLE RUBBER CEMENT

DESCRIPTION :

Apollo Sprayable Rubber Cement is a rubberized glue that offers outstanding bonding strength, used to join paper boards, leather, rubber and other materials.

DIRECTION FOR USE :

Clean the surface to be joined, then apply two coats of Apollo Sprayable Rubber Cement on both surface. Let dry for at least 2 minutes before joining the pieces together.

For strong materials, hammer it to make the joint more firm. If article is porous, apply third coat of sprayable rubber cement after 5 minutes and let dry for another 2 minutes before sticking the two pieces together.

COLOR :

Pale Yellow – Reddish Yellow

TYPICAL CHEMICAL AND PHYSICAL PROPERTIES :

Base Material : Rubber

Viscosity : 60 ± 5 ku

Total Solids % Wt. : 10 ± 2

Solvents : Aromatics / Ketone

PACKAGING :

18 Liter tin

CAUTION / INSTRUCTION :

Keep container closed when not in use. Mixture is flammable, do not use near fire.

SALE TO MINORS NOT ALLOWED.

The information in this data sheet is based on our current knowledge and experience. In view of the many factors that may affect processing and application, these data do not relieve users from the responsibility of carrying out their own tests neither do they imply any legally binding assurance of certain properties or suitability for a specific purpose. It is the responsibility of those to whom we supply our products to ensure that any propriety rights and existing laws and legislation are observed.

