



TECHNICAL DATA SHEET

GI PLASTIC SHELLAC

DESCRIPTION :

GI Plastic Shellac is a high quality varnish having amazing gloss, good adhesion and long lasting brightness and color.

USE :

Wood furniture and fixtures.

APPEARANCE :

Yellowish

FINISH :

Glossy

APPLICATION METHOD :

1. Prepare surface to be painted by sanding to obtain a finer wood grain.
2. Clean and keep surface dry. Remove all loose and foreign materials.
3. Shake well, bottle contents, then apply 2 – 3 coats by rubbing with a soft dry cloth dipped occasionally with GI Shellac Varnish.
4. Apply another coat of GI Shellac Varnish using same procedure.

DRYING TIME :

Dry to touch : 2 - 3 minutes

Dry to handle : 5 - 10 minutes

Dry hard : 15 –20 minutes

COVERAGE :

3 – 4 sq. m. / L

PACKAGING :

350cc bottle

The information in this data sheet is based on our current knowledge and experience. In view of the many factors that may affect processing and application, these data do not relieve users from the responsibility of carrying out their own tests neither do they imply any legally binding assurance of certain properties or suitability for a specific purpose. It is the responsibility of those to whom we supply our products to ensure that any propriety rights and existing laws and legislation are observed.

